



TECHNICAL DATA

Application	parks, pedestrians, bicycle routes
Assembly	pole top mounted or on extension arms with \varnothing 60 x 50 mm ending
Colour	cap - anodized inox, base - painted RAL 9006
Ingress protection	IP 66
Material	cap - formed aluminium sheet diffuser - frosted (PMMA) base - high-pressure die-casted aluminium alloy, painted
Expected useful lifetime	L90B10 - 100 000 h
CRI	>70
Input voltage frequency	50/60Hz
Power factor	\geq 0.95
Number of LED	16
Control system	Luminaire has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1- 10V).



TABLE OF TYPES

Code	Symbol	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux ¹	Luminaire luminous flux ¹	Luminous efficacy ¹	Unit volume	Net weight
214650/1	ATLANTIS LED	38 W	42 W	800 mA	2700 K	5850 lm	4850 lm	115 lm/W	0.22 m ³	4.1 kg
214650/3	ATLANTIS LED	38 W	42 W	800 mA	3500 K	6200 lm	5150 lm	123 lm/W	0.22 m ³	4.1 kg
214650/4	ATLANTIS LED	38 W	42 W	800 mA	4000 K	6700 lm	5550 lm	132 lm/W	0.22 m ³	4.1 kg
214650/6	ATLANTIS LED	38 W	42 W	800 mA	5000 K	6700 lm	5550 lm	132 lm/W	0.22 m ³	4.1 kg

1) tolerance +/- 5% due to LEDs accuracy

DIRECTIVES AND STANDARDS

DIRECTIVES: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC


STANDARDS: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2013, PN-EN 61547: 2009, PN-EN 61000-3-2: 2014, PN-EN 61000-3-3: 2013

CHARGING DISCHARGE FROM THE LED LUMINAIRE HOUSING


In order to efficient discharge the electrostatic charge from the housing of LED fitting installed on the pole from dielectric material (non-conductive) one of the following solutions is required:

- functional grounding
- LED luminaire with an additional protection device

TECHNICAL DRAWING



PHOTOMETRIC CURVES



POWER SYSTEM FUNCTIONS

Luminaire in standard has following functions of intelligent power supply:

- Connection to outside control system by DALI interface (operation of analog signal 1-10V as an option),
- Possibility of programming multistage dimming of luminaire, up to 5 intervals in the range of from 10 to 100% of nominal power,
- Temperature protection of LED module (from overheating) in case of unintentional luminaire operation during the,
- Regulation of power / luminous flux – the option of setting another value than the catalogue in the range of 30-100% of nominal one,

ACCETABLE QUANTITY OF LUMINAIRES ON ONE CIRCUIT

Accetable quantity of luminaires ATLANTIS LED on one circuit, protected by:

Overcurrent switches MCB type B or C

Oprawa	Typ	2A	4A	6A	10A	16A	20A	25A
ATLANTIS LED	B	4	7	12	18	30	37	46
	C	4	12	18	31	51	62	78

Fuse – type gG and GL

Oprawa	2A	4A	6A	10A	16A	20A	25A
ATLANTIS LED	1	10	20	26	52	71	101