



Installation: surrounding office buildings, parks, pedestrians

Ingress protection: IP 65

Material: anodised aluminium alloy

Operating temperature range: from -40°C to +55°C

Expected useful lifetime: L90F10 – 50 000 h, L80F20 – 100 000 h

CRI: >70 for 5000K; >80 for 3500K

Corrective factor S/P: 1,8 for 5000K; 1,45 for 3500K

Input voltage frequency: 50 - 60Hz

Power factor: ≥ 0.95

Inrush electric current: –

FLARE LED has the possibility to connect to an external control system via DALI interface (optionally via analog signal 1- 10V).



Code	Symbol	LED power	Luminaire Power consumption	Colour temperature (CCT)	Luminaire luminous flux ¹⁾	Luminous efficacy	Unit volume	Concrete footing / reinforcement basket type	Net weight
45280/6/C...	FLARE LED 1	14W	16W	5000K	750lm	54lm/W	0,027m ³	B-0A / Z-0A	8kg
45280/3/C...	FLARE LED 1	14W	16W	3500K	750lm	54lm/W	0,027m ³	B-0A / Z-0A	8kg
45281/6/C...	FLARE LED 2	20W	22W	5000K	1400lm	71lm/W	0,029m ³	B-0A / Z-0A	9kg
45281/3/C...	FLARE LED 2	20W	22W	3500K	1400lm	71lm/W	0,029m ³	B-0A / Z-0A	9kg

/C... – choice of anodising colour

2) tolerance +/- 7% due to LEDs accuracy

Directive: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC

