



## TECHNICAL DATA

<b>Application</b>	aluminium columns with spigot endings Ø60 i Ø76 mm
<b>Assembly</b>	with 3 screws M5, after preparing mounting holes in the column
<b>Colour</b>	Blue, Green, Red, White
<b>Ingress protection</b>	IP 65 or IP 44 (after mounting on the column)
<b>Material</b>	PMMA (IP 44), HDPE (IP 65)
<b>Input voltage frequency</b>	50/60Hz



## TABLE OF TYPES

Code	Symbol	LED power	Luminaire power consumption	Colour	Ingress protection	Mounting diameter	Net weight
40530	Small light spike	6 W	7 W	• White	IP 65	76 mm	0.6 kg
40520	Small light spike	6 W	7 W	• Red	IP 65	76 mm	0.6 kg
40510	Small light spike	6 W	7 W	• Green	IP 65	76 mm	0.6 kg
40500	Small light spike	6 W	7 W	• Blue	IP 65	76 mm	0.6 kg
4053	Small light spike	1 W	1.2 W	• White	IP 44	76 mm	0.5 kg
4052	Small light spike	1 W	1.2 W	• Red	IP 44	76 mm	0.5 kg
4051	Small light spike	1 W	1.2 W	• Green	IP 44	76 mm	0.5 kg
4050	Small light spike	1 W	1.2 W	• Blue	IP 44	76 mm	0.5 kg
4037	Small light spike	1 W	1.2 W	• White	IP 44	60 mm	0.5 kg
4036	Small light spike	1 W	1.2 W	• Red	IP 44	60 mm	0.5 kg
4035	Small light spike	1 W	1.2 W	• Green	IP 44	60 mm	0.5 kg
4034	Small light spike	1 W	1.2 W	• Blue	IP 44	60 mm	0.5 kg

# SMALL LIGHT SPIKE

