


## TECHNICAL DATA

|                    |  |
|--------------------|--|
| <b>Anodising</b>   | 10 colours   |
| <b>Packing</b>     | sleeve material  |
| <b>Purpose</b>     | aluminium columns with spigot endings $\varnothing 60 \times 180$  |
| <b>Application</b> | for mounting on SAL aluminium columns with ending $\varnothing 60 \times 180$ mm spigot  |
| <b>Finish</b>      | grinded, anodised aluminium  |
| <b>Material</b>    | anodised aluminium alloy   |
| <b>CE</b>          | the extension arm with the pole make a set - for extension arms, the Declaration of Performance applies to the pole on which extension arms is mounted |



## TABLE OF TYPES

| Code          | Symbol          | Purpose   | Number of arms | Unit volume         | Effective projected area | Luminaire mounting diameter | Outreach length - L | Height of extension arm - Z | Net weight |
|---------------|-----------------|---|----------------|---------------------|--------------------------|-----------------------------|---------------------|-----------------------------|------------|
| 47219111/C... | WRP 1/1,0/0,7/5 | aluminium columns with spigot endings $\varnothing 60 \times 180$ | 1              | 0.05 m <sup>3</sup> | 0.106 m <sup>2</sup>     | $\varnothing 60$ mm         | 1 m                 | 0.68 m                      | 3.7 kg     |

