



TECHNICAL DATA

Application	pedestrian crossings
Assembly	on column with ø60x50 mm ending
Colour	inox / black
Ingress protection	IP 66 for the optical part and the driver
Optical system	PMMA optics
Material	anodised aluminium alloy
Operating temperature range	from -40°C to +55°C (for 36 W), from -40°C to +40°C (for 45 W)
Expected useful lifetime	L90B10 - 100 000 h
Inrush current	50A / 210µs
Input voltage frequency	50/60Hz
Power factor	≥0.95
Number of LED	12
Control system	Luminaire has the possibility to connect to an external control system via analog signal 1- 10V.



TABLE OF TYPES

Code	Symbol	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux ¹	Luminaire luminous flux ¹	Luminous efficacy ¹	Unit volume	Net weight
2133032/1/... ²	ISKRA LED P 36 ALFA	36 W	39.5 W	960 mA	2700 K	5350 lm	4900 lm	124 lm/W	0.01 m ³	2.5 kg
2133032/3/... ²	ISKRA LED P 36 ALFA	36 W	39.5 W	960 mA	3500 K	5700 lm	5200 lm	132 lm/W	0.01 m ³	2.5 kg
2133032/4/... ²	ISKRA LED P 36 ALFA	36 W	39.5 W	960 mA	4000 K	6050 lm	5550 lm	141 lm/W	0.01 m ³	2.5 kg
2133032/6/... ²	ISKRA LED P 36 ALFA	36 W	39.5 W	960 mA	5000 K	6050 lm	5550 lm	141 lm/W	0.01 m ³	2.5 kg
2133045/1/... ²	ISKRA LED P ALFA 45	45 W	52 W	1250 mA	2700 K	6400 lm	5850 lm	113 lm/W	0.01 m ³	2.5 kg
2133045/3/... ²	ISKRA LED P ALFA 45	45 W	52 W	1250 mA	3500 K	6800 lm	6250 lm	120 lm/W	0.01 m ³	2.5 kg
2133045/4/... ²	ISKRA LED P ALFA 45 - 4000K	45 W	52 W	1250 mA	4000 K	7200 lm	6600 lm	127 lm/W	0.01 m ³	2.5 kg
2133045/6/... ²	ISKRA LED P ALFA 45 - 5000K	45 W	52 W	1250 mA	5000 K	7200 lm	6600 lm	127 lm/W	0.01 m ³	2.5 kg

1) tolerance +/- 7% due to LEDs accuracy


: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC
: PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2013, PN-EN 61547: 2009, PN-EN 61000-3-2: 2014, PN-EN 61000-3-3: 2013

In order to efficient discharge the electrostatic charge from the housing of LED fitting installed on the pole from dielectric material (non-conductive) one of the following solutions is required:

- functional grounding
- LED luminaire with an additional protection device


ISKRA LED P ALFA

na przejścia dla pieszych dla dróg z ruchem prawostronnym




ISKRA LED P ALFA

na przejścia dla pieszych dla dróg z ruchem lewostronnym




P - ISKRA LED P



cd/klm
— C0 - C180 - - - C90 - C270

L - ISKRA LED P



cd/klm
— C0 - C180 - - - C90 - C270

The luminaire can optionally be connected to an external control system via the 1-10V interface.

The standard functions of the intelligent power supply system are provided by the ISKRA LED PROG and ISKRA LED ALFA PROG luminaires