




## TECHNICAL DATA

<b>Application</b>	pedestrian crossings
<b>Assembly</b>	on extension arms with $\varnothing$ 60 x 90 mm ending
<b>Colour</b>	inox / black
<b>Ingress protection</b>	IP 66 for the optical part and the driver
<b>Optical system</b>	PMMA optics
<b>Material</b>	anodised aluminium alloy
<b>Operating temperature range</b>	from -40°C to +55°C (for 36 W), from -40°C to +40°C (for 45 W)
<b>Expected useful lifetime</b>	L90B10 - 100 000 h
<b>CRI</b>	>70
<b>Inrush current</b>	50A / 210 $\mu$ s
<b>Input voltage frequency</b>	50/60Hz
<b>Power factor</b>	$\geq$ 0.95
<b>Number of LED</b>	12
<b>Control system</b>	Luminaire has the possibility to connect to an external control system via analog signal 1- 10V.



## TABLE OF TYPES

Code	Symbol	LED power	Luminaire power consumption	LED forward current	Colour temperature (CCT)	LEDs luminous flux <sup>1</sup>	Luminaire luminous flux <sup>1</sup>	Luminous efficacy <sup>1</sup>	Unit volume	Net weight
2132032/1/... <sup>2</sup>	ISKRA LED P 36	36 W	39.5 W	960 mA	2700 K	5350 lm	4900 lm	124 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132032/3 /... <sup>2</sup>	ISKRA LED 36 P	36 W	39.5 W	960 mA	3500 K	5700 lm	5200 lm	132 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132032/4 /... <sup>2</sup>	ISKRA LED 36 P	36 W	39.5 W	960 mA	4000 K	6050 lm	5550 lm	141 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132032/6 /... <sup>2</sup>	ISKRA LED 36 P	36 W	39.5 W	960 mA	5000 K	6050 lm	5550 lm	141 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132045/1/... <sup>2</sup>	ISKRA LED P 45	45 W	52 W	1250 mA	2700 K	6400 lm	5850 lm	124 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132045/3 /... <sup>2</sup>	ISKRA LED 45 P	45 W	52 W	1250 mA	3500 K	6800 lm	6250 lm	132 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132045/4 /... <sup>2</sup>	ISKRA LED 45 P	45 W	52 W	1250 mA	4000 K	7200 lm	6600 lm	141 lm/W	0.005 m <sup>3</sup>	2.1 kg
2132045/6 /... <sup>2</sup>	ISKRA LED 45 P	45 W	52 W	1250 mA	5000 K	7200 lm	6600 lm	141 lm/W	0.005 m <sup>3</sup>	2.1 kg

1) tolerance +/- 7% due to LEDs accuracy

## DIRECTIVES AND STANDARDS

**DIRECTIVES:** 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC

**STANDARDS:** PN-EN IEC 60598-1: 2021-7, PN-EN 60598-2-3: 2006, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 62471:2010, PN-EN 55015: 2013, PN-EN 61547: 2009, PN-EN 61000-3-2: 2014 , PN-EN 61000-3-3: 2013



## CHARGING DISCHARGE FROM THE LED LUMINAIRE HOUSING

In order to efficient discharge the electrostatic charge from the housing of LED fitting installed on the pole from dielectric material (non-conductive) one of the following solutions is required:



- functional grounding
- LED luminaire with an additional protection device

## TECHNICAL DRAWING

crosswalks for roads with right-hand traffic




crosswalks for roads with left-hand traffic




## PHOTOMETRIC CURVES

P - ISKRA LED P



cd/klm  
— C0 - C180    - - - C90 - C270

L - ISKRA LED P



cd/klm  
— C0 - C180    - - - C90 - C270

## POWER SYSTEM FUNCTIONS

The luminaire can optionally be connected to an external control system via the 1-10V interface.

The standard functions of the intelligent power supply system are provided by the ISKRA LED PROG and ISKRA LED ALFA PROG luminaires