



TECHNICAL DATA

Application	aluminium columns with spigot endings Ø60 i Ø76 mm
Assembly	with 3 screws M6, after preparing mounting holes in the column
Colour	Blue, Green, Red, White
Ingress protection	IP 65 or IP 44 (after mounting on the column)
Material	PMMA (IP 44), HDPE (IP 65)
Input voltage frequency	50/60Hz



TABLE OF TYPES

Code	Symbol	LED power	Luminaire power consumption	Colour	Ingress protection	Mounting diameter	Net weight
40530	Small light spike	6 W	7 W	• White	IP 65	76 mm	0.6 kg
40520	Small light spike	6 W	7 W	• Red	IP 65	76 mm	0.6 kg
40510	Small light spike	6 W	7 W	• Green	IP 65	76 mm	0.6 kg
40500	Small light spike	6 W	7 W	• Blue	IP 65	76 mm	0.6 kg
4053	Small light spike	1 W	1.2 W	• White	IP 44	76 mm	0.5 kg
4052	Small light spike	1 W	1.2 W	• Red	IP 44	76 mm	0.5 kg
4051	Small light spike	1 W	1.2 W	• Green	IP 44	76 mm	0.5 kg
4050	Small light spike	1 W	1.2 W	• Blue	IP 44	76 mm	0.5 kg
4037	Small light spike	1 W	1.2 W	• White	IP 44	60 mm	0.5 kg
4036	Small light spike	1 W	1.2 W	• Red	IP 44	60 mm	0.5 kg
4035	Small light spike	1 W	1.2 W	• Green	IP 44	60 mm	0.5 kg
4034	Small light spike	1 W	1.2 W	• Blue	IP 44	60 mm	0.5 kg

SMALL LIGHT SPIKE

