



TECHNICAL DATA

Application	aluminium columns with spigot endings Ø60 i Ø76 mm
Assembly	with 3 screws M5, after preparing mounting holes in the column
Colour	Blue, Green, Red, White
Ingress protection	IP 65 or IP 44 (after mounting on the column)
Material	PMMA (IP 44), HDPE (IP 65)
Input voltage frequency	50/60Hz



TABLE OF TYPES

Code	Symbol	LED power	Luminaire power consumption	Colour	Ingress protection	Mounting diameter	Net weight
40490	Light ball	6 W	7 W	• White	IP 65	76 mm	0.6 kg
40480	Light ball	6 W	7 W	• Red	IP 65	76 mm	0.6 kg
40470	Light ball	6 W	7 W	• Green	IP 65	76 mm	0.6 kg
40460	Light ball	6 W	7 W	• Blue	IP 65	76 mm	0.6 kg
4049	Light ball	1 W	1.2 W	• White	IP 44	76 mm	0.4 kg
4048	Light ball	1 W	1.2 W	• Red	IP 44	76 mm	0.4 kg
4047	Light ball	1 W	1.2 W	• Green	IP 44	76 mm	0.4 kg
4046	Light ball	1 W	1.2 W	• Blue	IP 44	76 mm	0.4 kg
4033	Light ball	1 W	1.2 W	• White	IP 44	60 mm	0.4 kg
4032	Light ball	1 W	1.2 W	• Red	IP 44	60 mm	0.4 kg
4031	Light ball	1 W	1.2 W	• Green	IP 44	60 mm	0.4 kg
4030	Light ball	1 W	1.2 W	• Blue	IP 44	60 mm	0.4 kg

LIGHT BALL

