



TECHNICAL DATA

Application	parks, pedestrians
Assembly	on columns, extension arms, aluminium and steel wall brackets with spigot ending $\varnothing 60$ mm, 70 mm deep and on poles type S and SP with special adaption for this luminaire
Colour	black
Ingress protection	IP 44
Material	polyamide with fibre glass
Input voltage frequency	50/60Hz
Supply voltage	230V AC
Mounting method	only upwards
Type of luminaires	OZ 400 - lamp's diffuser collar diameter $\varnothing 180$ mm




TABLE OF TYPES

Code	Symbol	Power	Unit volume	Effective projected area	Colour	Light source type	Lamp diffuser neck	Type of diffuser	Net weight
211415	OZ 400	23 W	0.01 m ³	0.13 m ²	• black	LED E-27	180 mm	Sphere 400, Klio 400	0.35 kg

: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC
 : PN-EN 60598-1: 2015, PN-EN 60529: 2003, PN-EN 62262: 2003, PN-EN 55015: 2013, PN-EN 61547: 2009, PN-EN 61000-3-2: 2014, PN-EN 61000-3-3: 2013,

TECHNICAL DRAWING

